

ATOM

EXTREMELY COMPACT AND COMFORTABLE

Compact, lightweight and extremely comfortable thanks to its modular TPR frame, the ATOM offers enhanced protection.
Use: safety goggles or face shield.

PLATINUM



71 g

OPTIONAL

optical insert
SOSATOM



Protective films pack of 5
TOATOM



ATOM + VISOR



ATOM DOUBLE LENS



ATOAPSI



ATOEPSI



ATOFAPSI



ATOV



SOSATOM



TOATOM



ATOEDEPSI

- + THERMO PLASTIC RUBBER (TPR)**
- + OVERFLOW CHUTE FOR LIQUIDS**
- + BALL-PIVOT**
- + ADJUSTABLE STRAP**
- + FITS OVER PRESCRIPTION GLASSES**

bolle
SAFETY

ATOM

EXTREMELY COMPACT AND COMFORTABLE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
ATOM	Ventilated	ATOAPSI	2C-1,2 ☞ 1 BT KN C€	☞ EN166 3 BT C€	Anti-scratch/Anti-fog(☞)
	Sealed	ATOEPSI	2C-1,2 ☞ 1 BT KN C€	☞ EN166 3 4 5 BT C€	Anti-scratch/Anti-fog(☞)
	Breathable foam	ATOFAPSI	2C-1,2 ☞ 1 BT KN C€	☞ EN166 3 BT C€	Anti-scratch/Anti-fog(☞)
	Sealed double lens	ATOEDEPSI	2C-1,2 ☞ 1 BT KN C€	☞ EN166 3 4 5 BT C€	Anti-scratch/Anti-fog(☞)
	Visor for ATOM	ATOV	-	☞ EN166 3 BT C€	-
	RX insert	SOSATOM	C€	-	-
	Protective film	TOATOM	C€	-	-

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

K. Resistance to surface damage by fine particles (optional)

N. Resistance to fogging (optional)

C€ European standard ☞ Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets or splashes.

4. Large dust particles > 5 microns.

5. Gas and fine dust particles < 5 microns.

B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard ☞ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

EQUALIZER

Equalizer is the high performance goggle system for protecting against fog, thanks to its double lens and regulation patch, the equalizer filters and regulates moisture levels in the goggles.

PLATINUM

This permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd/m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes.

In all circumstances and at all times the PLATINUM lens innovation guarantees your eyes improved protection.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.



Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY