B808 PROTECTIVE AND LIGHTWEIGHT

The best seller in the prescription line, the B808 is now available in the spectacle range. Lightweight, stylish and wrap-around, the B808 is a guaranteed success!



BOOBLPSI

SAFETY

28 g

+ UPPER AND SIDE PROTECTION

+ WRAP-AROUND FIT

B808 PROTECTIVE AND LIGHTWEIGHT

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
B808	Clear	B808BLPSI	2C-1,2 🗁 1 F KN CE	🗁 EN166 F C €	Anti-scratch/Anti-fog (*₽)

LENS MARKING

Optical class symbols: 1. Continuous work

Mechanical strength symbols:F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

Others symbols:

 ${\bf K}.$ Resistance to surface damage by fine particles

N. Resistance to fogging
C€ European standard ☆ Manufacturer name

TECHNOLOGY

Individual plastic

bag 10 safety spectacles

per inner box

240 safety spectacles pe outer pack

afac

₽LATINUM

The new exclusive scratch and fog resistant coating guarantees even more safety, reliability and comfort. Washabile (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

PACKAGING AND EAN13 CODE

B808BLPSI

3660740007218

3660740107215

3660740207212

U.K. Bollé Safety

Surrey - KT9 2NY

Tél. : 00 44 (0)208 391 4700

Fax: 00 44 (0)208 391 4733

e-mail : sales@bolle-safety.co.uk

Unit C83 - Barwell Business Park Leatherhead Road - Chessington

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.
F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

C€ European standard ☆ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly with a mild soap detergent or optical solution.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHA	RACTERISTICS
LENSES	PC - 2,2 mm - Curve 4
FRAME	PC
TEMPLES	PC
STRAP	No
FOAM	No
SPARE LENSES	No

-contractual pictures 21/05/2014



Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél. : 00 33 (0) 4 78 85 23 64 Fax : 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

bolle-safety.com