

# B-LINE

B-LINE is a safety eyewear range available to all and geared to the most common industrial risks. B-LINE showcases Bollé safety expertise and quality.

**B LINE**



BL10CI




BL11CI-PI



BL15API-APSI



BL13CI



BL20PI



BL20HA

**+ B-LINE IS A SAFETY EYEWEAR RANGE AVAILABLE TO ALL**

**bolle**  
SAFETY

# B-LINE

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
B-LINE	SAFETY SPECTACLES	BL10CI	2C-1,2 ☞ 1 FT C€	☞ EN166 FT C€	Anti-scratch
		BL10CF	5-2,5 ☞ 1 FT C€	☞ EN166 FT C€	Anti-scratch
		BL10WPCC5	5 ☞ 1 FT C€	☞ EN166 FT C€	-
		BL11PI	2-1,2 ☞ 1 FT C€	☞ EN166 FT C€	-
		BL11CI	☞ 1 FT C€	☞ EN166 FT C€	Anti-scratch
		BL13CI	2-1,2 ☞ 1 FT C€	☞ EN166 FT C€	Anti-scratch
		BL13CF	5-2,5 ☞ 1 FT C€	☞ EN166 FT C€	Anti-scratch
	SAFETY GOGGLES	BL15API	☞ 1 FT C€	☞ EN166 FT C€	-
		BL15APSI	2-1,2 ☞ 1 FT C€	☞ EN166 FT C€	Anti-fog
	FACE SHIELDS	BL20PI	☞ 1 B C€	☞ EN166 B C€	-
		BL20FAPI	☞ 1 B C€	-	-
		BL20HA	-	☞ EN1731 C€	-

## LENS MARKING

**Optical class symbols:**

**1.** Continuous work

**Mechanical strength symbols:**

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**Others symbols:**

C€ European standard ☞ Manufacturer name

## FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard ☞ Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.



Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**bolle-safety.com**

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY