CHRONOSOFT POMPIER

ULTIMATE PROTECTION

Ideal for fire fighting, CHRONOSOFT goggles offer high-end innovation. The elastomer frame withstands extreme heat. The double lens features the EQUALIZER system for effective fog protection.



TEMPERATURE RESISTANCE

Frame: 170°C Lens: 135°C Buckle: 150°C Strap: 110°C



CHROKADESI



- **+** DOUBLE LENS (POLYCARBONATE INNER & OUTER LENS)
- **+** FOR FIRE FIGHTING OR EXTREME TEMPERATURES
- + LARGE ADJUSTABLE STRAP



CHRONOSOFT POMPIER

ULTIMATE PROTECTION

| MODEL | VERSIONS | REFERENCES | LENS MARKING | FRAME MARKING | COATINGS |
|-----------------------|----------|------------|-----------------------|-----------------------|-----------------------------|
| CHRONOSOFT POMPIER | Sealed | CHROKADESI | 2C-1,2 🗁 1 BT 9 KN €€ | ₩ EN166 3 4 5 9 BT C€ | Anti-scratch(K)/Anti-fog(N) |

LENS MARKING

Optical class symbols:

1. Continuous work

Use symbols:

9. Molten metal and hot solids.

Mechanical strength symbols:

- B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

- K. Resistance to surface damage by fi ne particles (optional)
- N. Resistance to fogging (optional)
- C€ European standard ☐ Manufacturer name

TECHNOLOGY

∠EQUALIZER

Equalizer is the high performance goggle system for protecting against fog. thanks to its double lens and regulation patch, the equalizer filters and regulates moisture levels in the googles.

| PACKAGING AND EAN 13 CODE | | | | |
|-------------------------------------|---------------|--|--|--|
| | CHROKADESI | | | |
| Individual plastic bag and box | 3660740000738 | | | |
| 60 safety goggles per outer pack | 3660740200732 | | | |

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- 3. Liquid droplets or splashes.
- 4. Large dust particles > 5 microns.
- 5. Gas and fine dust particles < 5 microns.
- 9. Molten metal and hot solids.
- B. Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment

| CHARACTERISTICS | | | | |
|-----------------|--|--|--|--|
| LENSES | PC 1,1 mm (inside) PC 2,1 mm (outside) Curve 6 | | | |
| FRAME | Kraton / TPR | | | |
| TEMPLES | Non applicable | | | |
| STRAP | Polyamide, Polyester, Latex | | | |
| FOAM | No | | | |
| SPARE LENSES | No | | | |











01/10/2013

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax: 00 44 (0)208 391 4733
e-mail : sales@holle-safety.co.uk

