CONTOUR METAL

STYLISH AND EFFECTIVE

METAL version Contour: success guaranteed!





CONTMPSI



CONTMPSF



CONTMESP



SUPPLIED WITH

Microfibre pouch **ETUIFS**



- INCREASED UPPER PROTECTION
- **+** NON-SLIP TIPGRIP TEMPLES
- + 160% FLEX TEMPLES
- + ADJUSTABLE NON-SLIP BRIDGE
- + ANTI-STATIC



CONTOUR METAL

STYLISH AND EFFECTIVE

	MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
		Clear	CONTMPSI	2C-1,2 😭 1 FT €€	≌ EN166 FT C€	Anti-scratch/anti-fog
	CONTOUR MÉTAL	Smoke	CONTMPSF	5-3,1 😭 1 FT €€	≅ EN166 FT C€	Anti-scratch/anti-fog
		ESP	CONTMESP	5-1,4 😭 1 FT C€	≅ EN166 FT C€	Anti-scratch

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

TECHNOLOGY

∠ESP

ESP, Extra Sensory Perception. An innovative coating to reduce dazzle and the harmful affects of blue light. B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB

PACKAGING AND EAN13 CODE							
	CONTMPSI	CONTMPSF	CONTMESP				
Individual plastic bag	3660740003777	3660740003784	3660740003791				
10 safety spectacles per inner box	3660740103774	3660740103781	3660740103798				
240 safety spectacles per outer pack	3660740203771	3660740203788	3660740203795				

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- C€ European standard ☐ Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environmen

CHARACTERISTICS				
LENSES	PC - 2,3 mm - Curve 9,25			
FRAME	Metal nickel free			
TEMPLES	Metal nickel free + TPE			
STRAP	Non applicable			
FOAM	Non applicable			
SPARE LENSES	No			











02/02/2018

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY Tél.: 00 44 (0)208 391 4700

Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

