

RUSH

THE COMFORT OF PANORAMIC VISION

Available in twilight version, the panoramic and lightweight RUSH model offers perfect optical quality, permanent comfort and modern design.



25 g

SUPPLIED WITH

Adjustable cord
CORDC



+ UPPER PROTECTION

+ ADJUSTABLE NON-SLIP BRIDGE

+ NON-SLIP TEMPLES

bolle
SAFETY



RUSHPSI



RUSHPSF



RUSHDPI



RUSHTWI



* RUSHKITFS
Foam & Strap Kit (The
foam is compatible with
RUSH & RUSH+ Models
// The strap is only com-
patible with RUSH+)

RUSH

THE COMFORT OF PANORAMIC VISION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
RUSH	Clear	RUSHPSI	2C-1,2 1 FT €€	EN166 FT €€	Anti-scratch/anti-fog
	Smoke	RUSHPSF	5-3,1 1 FT €€	EN166 FT €€	Anti-scratch/anti-fog
	HD	RUSHDPI	2C-1,2 1 FT €€	EN166 FT €€	Hydrophobic/anti-scratch
	Twilight	RUSHTWI	5-2 1 FT €€	EN166 FT €€	Anti-scratch/anti-fog
	* Foam & Strap Kit	RUSHKITFS	-	-	-

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol,
authorises use for high speed particles at extreme temperatures.

Others symbols:

€€ European standard 1 Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against
everyday risks including dropping the protective eyewear onto the ground,
ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises
use for high speed particles at extreme temperatures.

€€ European standard 1 Manufacturer name

**Bollé Safety product approval certificates to CE standards will be
sent on request.**

TECHNOLOGY

BHD

A revolutionary coating for exceptional
clarity and light transmission. Its visible
light transmission rate is 96% compared
with 90% for conventional clear lenses.

B-TWILIGHT

The new B-Twilight technology offers the
advantages of ESP with a double anti-fog
coating (on both sides of the lenses) to prevent
fogging in the most challenging conditions.
Designed and used in low light conditions, it
improves contrast. Its light transmission rate is
perfect for outdoors, particularly early morning
and late evening. B-Twilight filters 76% of blue
light.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using
the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the
complete product. If the frame is damaged also replace the complete product. After each
use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE					
	RUSHDPI	RUSHPSI	RUSHPSF	RUSHTWI	RUSHKITFS
Individual plastic bag	366074000097	366074000648	366074000665	366074000662	366074000648
10 safety spectacles per inner box	3660740100094	3660740106645	3660740106652	3660740106669	3660740106485
240 safety spectacles per outer pack	3660740200091	3660740206642	3660740206659	3660740206666	3660740206482

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC + PVC
STRAP	Non applicable
FOAM	SBR
SPARE LENSES	No



Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY

16/09/2014