SPIDER

SPORTY LOOK

The only model available in the red flash SPIDER provides protection for outdoor activities.













Microfibre pouch **FTUIFS**



- + NON-SLIP BRIDGE
- + LOWER PROTECTION
- NON-SLIP TIPGRIP TEMPLES



SPIDER

SPORTY LOOK

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
	Clear	SPIPSI	2C-1,2 😭 1 FT KN C€	≌ EN166 FT C€	Anti-scratch(K)/anti-fog(N)
SPIDER	ESP	SPIESP	5-1,4 😭 1 FT K C€	≌ EN166 FT C€	Anti-scratch(K)/anti-fog
	Red flash	SPIFLASH	5-3,1 😭 1 FT K C€	≅ EN166 FT C€	Anti-scratch(K)/anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

- K. Resistance to surface damage by fine particles (optional)
- N. Resistance to fogging (optional)
- C€ European standard ☐ Manufacturer name

TECHNOLOGY

∠ESP

ESP, Extra Sensory Perception.
An innovative coating to reduce dazzle and the harmful affects of blue light. B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

PACKAGING AND EAN13 CODE							
	SPIPSI	SPIESP	SPIFLASH				
Individual plastic bag	3660740003210	3660740003227	3660740003234				
10 safety spectacles per inner box 3660740103217		3660740103224	3660740103231				
300 safety spectacles per outer pack	3660740203214	3660740203221	3660740203238				

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 8			
FRAME	PC			
TEMPLES	Nylon + TPE			
STRAP	Non applicable			
FOAM	Non applicable			
SPARE LENSES	No			











01/10/2013

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél : 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@holle-safety.com

bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY Tél : 00 44 (0)208 391 4700

Fax: 00 44 (0)208 391 4733 e-mail · sales@holle-safety.co.uk

