VOODO

COMBINING STYLE AND PROTECTION



VODNESE



VODRESE



VODRPOL



Microfibre pouch **FTUIFS**



- + SIDE SHIELDS
- + NON-SLIP BRIDGE
- **+** NON-SLIP TEMPLES



VOODOO

COMBINING STYLE AND PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
V00D00	Smoke	VODNPSF	5-3,1 😭 1 FT C€	≌ EN166 FT C€	Anti-scratch/anti-fog
	Brown	VODBPSB	5-3,1 😭 1 FT C€		Anti-scratch/anti-fog
	Brown Polarized	VODBPOL	5-3,1 🖆 1 FT C€		Anti-scratch/anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard ☐ Manufacturer name

TECHNOLOGY

△POLARIZED

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB

PACKAGING AND EAN13 CODE							
	VODNPSF	VODBPSB	VODBPOL				
Individual plastic bag	3660740006617	3660740006624	3660740006631				
10 safety spectacles per inner box	3660740106614	3660740106621	3660740106638				
240 safety spectacles per outer pack	3660740206611	3660740206628	3660740206635				

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS		
LENSES	PC 2,2 mm Curve 8	
FRAME	Nylon	
TEMPLES	Nylon + insert PAD EVA	
STRAP	Non applicable	
FOAM	Non applicable	
SPARE LENSES	No	











U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessingtor

Tél : 00 44 (0)208 391 4700 Fax : 00 44 (0)208 391 4733 e-mail : sales@holle-safety.co.uk



69100 Villeurhanne - France

Tél : 00 33 (0) 4 78 85 23 64

Europe Bollé Safety

95 rue Louis Guérin

Surrey - KT9 2NY



01/10/2013