

SLAM

ULTRA-TRENDY

Stylish and easy-to-wear. The SLAM model provides protection at all times while offering unbeatable comfort.



- + WRAP-AROUND FIT
- + ALL-ROUND VISION
- + COMFORTABLE STRAIGHT TEMPLES

bolle
SAFETY

SLAM

ULTRA-TRENDY

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SLAM	Clear	SLAPSI	2C-1,2 1 FT €	EN166 FT €	Anti-scratch/anti-fog
	Smoke	SLAPSF	5-3,1 1 FT €	EN166 FT €	Anti-scratch/anti-fog
	Yellow	SLAPSJ	2C-1,2 1 FT €	EN166 FT €	Anti-scratch/anti-fog
	ESP	SLAESP	5-1,4 1 FT €	EN166 FT €	Anti-scratch
	Welding shade 1,7	SLAWPCC2	1,7 1 FT €	EN166 FT €	Anti-scratch
	Welding shade 3	SLAWPCC3	3 1 FT €	EN166 FT €	Anti-scratch
	Welding shade 5	SLAWPCC5	5 1 FT €	EN166 FT €	Anti-scratch

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

€ European standard Manufacturer name

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€ European standard Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

TECHNOLOGY

ESP

ESP, Extra Sensory Perception.
An innovative coating to reduce dazzle and the harmful affects of blue light.
B-ESP filters 57% of blue light, transmits 64% of visible light, 99.99% of UVA/UVB.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE								CHARACTERISTICS	
	SLAPSI	SLAPSF	SLAPSJ	SLAESP	SLAWPCC2	SLAWPCC3	SLAWPCC5	LENSES	PC - 2,3 mm - Curve 11
Individual plastic bag	3660740001087	3660740001094	3660740001100	3660740001117	3660740001124	3660740001131	3660740001148	FRAME	PC
10 safety spectacles per inner box	3660740101084	3660740101091	3660740101107	3660740101114	3660740101121	3660740101138	3660740101145	TEMPLES	PC
200 safety spectacles per outer pack	3660740201081	3660740201098	3660740201104	3660740201111	3660740201128	3660740201135	3660740201142	STRAP	Non applicable
								FOAM	Non applicable
								SPARE LENSES	No



Europe Bollé Safety
95 rue Louis Guérin
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : sales@bolle-safety.co.uk

bolle
SAFETY

01/10/2013