

# TRYON

## STYLE AND PERFORMANCE

New brand signature, TRYON is available in 3 versions : safety spectacles, OTG and prescription spectacles. Ultra-wrap-around, sporty design, co-injected FLEX 160° temples, adjustable and non-slip bridge, PLATINUM® coating... TRYON perfectly combines style, innovation and absolute protection.

**PLATINUM®**



TRYOPSI

TRYOPSF

TRYOCSP

TRYOFASH

RUSHKITS (option)  
Strap

26g

- + WRAP-AROUND FRAME**
- + PLATINUM® COATING (P)**  
**- EXCEPT FLASH VERSION**
- + CO-INJECTED PC/TPR TEMPLES**
- + NON-SLIP ADJUSTABLE BRIDGE**
- + FLEX 160° TEMPLES**

**bolle**  
SAFETY

# TRYON

## STYLE AND PERFORMANCE

| MODEL | VERSIONS            | REFERENCES | LENS MARKING      | FRAME MARKING | COATINGS                       |
|-------|---------------------|------------|-------------------|---------------|--------------------------------|
| TRYON | Clear               | TRYOPSI    | 2C-1,2 1 FT KN €€ | EN166 FT €€   | Anti-scratch/Anti-fog P        |
|       | CSP                 | TRYOCSP    | 5-1,4 1 FT KN €€  | EN166 FT €€   | Anti-scratch/Anti-fog P        |
|       | Smoke               | TRYOPSF    | 5-3,1 1 FT KN €€  | EN166 FT €€   | Anti-scratch/Anti-fog P        |
|       | Blue flash          | TRYOFASH   | 5-3,1 1 FT €€     | EN166 FT €€   | Anti-scratch/Anti-fog (inside) |
|       | Strap only (option) | RUSHKITS   | -                 | -             | -                              |

### LENS MARKING

**Optical class symbols:**

**1.** Continuous work

**Mechanical strength symbols:**

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**Others symbols:**

**K.** Resistance to surface damage by fine particles

**N.** Resistance to fogging

€€ European standard 1 Manufacturer name

### TECHNOLOGIES

**CSP**

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

**PLATINUM®**

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

€€ European standard 1 Manufacturer name

**Bolle Safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bolle Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

| PACKAGING AND EAN13 CODE             |               |               |               |               |               |
|--------------------------------------|---------------|---------------|---------------|---------------|---------------|
|                                      | TRYOPSI       | TRYOPSF       | TRYOCSP       | TRYOFASH      | RUSHKITS      |
| Individual plastic bag               | 3660740008260 | 3660740008277 | 3660740008284 | 3660740008437 | 3660740007546 |
| 10 safety spectacles per inner box   | 3660740108267 | 3660740108274 | 3660740108281 | 3660740108434 | 3660740107543 |
| 240 safety spectacles per outer pack | 3660740208264 | 3660740208271 | 3660740208288 | 3660740208431 | 3660740207540 |

| CHARACTERISTICS |                       |
|-----------------|-----------------------|
| LENSES          | PC - 2,2 mm - Curve 8 |
| FRAME           | -                     |
| TEMPLES         | PC + TPR              |
| STRAP           | Nylon/15mm/Adjustable |
| SPARE LENSES    | No                    |



Europe Bolle Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

**bolle-safety.com**

U.K. Bolle Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY

Non-contractual pictures

18/04/2017